

r/w	ADR	HEXADR	NAME	Description	Shadow	OS
write	53774	\$D20E	IRQEN	<a href="#">POKMSK</a>	Interrupt Request Enable	all
read	53774	\$D20E	IRQST	<a href="#">POKMSK</a>	Interrupt Request Status	all

## Write#

Bit	Function
0	d
1	d
2	d
3	d
4	d
5	d
6	d
7	d

Bit set to "0" (zero) turns interrupt off (disable) Bit set to "1" (one) turns interrupt on (enable)

## Read#

Bit	Value	Function	Vector
0	\$01 1	Timer 1 (counted down to zero)	<a href="#">VTIMR1</a> (528; \$0210)
1	\$02 2	Timer 2 (counted down to zero)	<a href="#">VTIMR2</a> (530; \$0212)
2	\$04 4	Timer 4 (counted down to zero)	<a href="#">VTIMR4</a> (532; \$0214 - OS "B" and later ROMs only)
3	\$08 8	Serial output transmission down	<a href="#">VSEROC</a> (526; \$020E)
4	\$10 16	Serial Output data needed	<a href="#">VSEROR</a> (524; \$020C)
5	\$20 32	Serial input data ready	<a href="#">VESRIN</a> (522; \$020A)
6	\$40 64	Other key pressed	<a href="#">VKEYBD</a> (520; \$0208)
7	\$80 128	Break key pressed	<a href="#">BRKKY</a> (566; \$0236 - OS "B" and later ROMs only)

see also: [Keyboard topics](#)

previous: [SERIN,SEROUT](#)

next: [SKCTL,SKSTAT](#)